

**PENNSYLVANIA ACTIVATED SLUDGE
WASTEWATER TREATMENT PLANT****Challenge:**

To determine if Enviro-Tech of America, Inc. and **PX-700®** could accomplish the following:

- Reduce amount of solids that are produced at the treatment plant
- Reduce the disposal cost of the sludge produced
- Improve the quality of the final effluent

Facility personnel were used to gather and maintain records for the appropriate data.

Background Data:

Facility Type: Activated Sludge
 Design Flow: 5.8 million gallons per day
 Current Flow: 8.0 million gallons per day

Treatment Procedure:

Product Used: **PX-700®**
 Treatment Period: 30 days
 Amount of Product Used: First four weeks at 53 ounces per day
 Injection Points: 966 ounces or 7.54 gallons per 24 hour period

Results:

	<u>Start</u>	<u>End</u>	<u>Reduction</u>
Biosolids Reduction	29 tons/week	18 tons/week	40%
Monthly Hauling Cost	\$27,964.57	\$16,875.00	\$11,089.57
Annual Hauling Cost	\$335,574.84	\$202,500.00	\$133,074.84
Effluent NH ₃ -N	431 lbs/day	282 lbs/day	35%
Effluent CL ₂ Residual	0.37 mg/L	0.27 mg/L	27%

The introduction of **PX-700®** into the facility at a controlled dosage of 1 ppm has enabled the facility to improve the overall effluent quality and significantly reduce biosolids and associated processing, hauling, and handling costs.

Another Cutting Edge Product through *Biological Activity* from

Enviro-Tech of America, Inc.

Office: 239-673-8280

Fax: 239-424-8408

The F.O.G. Experts

715 NE 19th Place; Unit 22

Cape Coral, FL 33909

info@envirotechofamerica.com

www.envirotechofamerica.com



A Veteran Owned Company